



43082 (ZB3003)

Zigbee, In-wall Smart Dimmer With Energy Monitoring

Key Features

- Turn the connected device On/Off manually or via Zigbee HA 3.0 certified controller
- Zigbee 3.0 Certified for simple pairing and integrated home automation
 - Backwards compatible with Zigbee HA 1.2 controllers/devices
- May be used in single pole installation or with up to four Enbrighten model 46199 Add-on switches in 3, 4, 5 or 6-way wiring configurations
- Blue LED indicates switch location in a dark room and when awaiting pairing with Zigbee Controller
- Energy Monitoring
 - Track Watts (W) and Kilowatt Hours (kWh) through the Zigbee Controller
- Can be Included in multiple Groups and Scenes
- Screw Terminal installation; requires wiring connections for Line (Hot), Load, Neutral and Ground. Traveler wire required for multi pole installation
- Uses a standard-size “Decora” style wall plate for single gang installations (wall plate not included)
- Interchangeable Paddle switch: White & light almond paddle in package
- LED can be enabled/disabled manually
- Inline traveler circuit protection
- UL listed to work with dimmable LED/CFL bulbs

QuickFit features:

- 20% Smaller Housing compared to previous models
- No Breakoff tabs on front yoke

SimpleWire features:

- Auto Detect Line/Load terminals
- Offset 2-wire ground terminal

SPECIFICATIONS

Power: 120 VAC, 60 Hz.

Signal (Frequency): 2.4 Ghz IEEE 802.15.4

Maximum Load: 600W, incandescent; 300W CFL/LED

Operating Temperature Range: 32-104° F (0-40° C)

For indoor use only.

cUL: ZB3003 / 43082

Contains FCC: QOQMGM13P

Contains IC: 5123A-MGM13P

JASCO Products

10 E. Memorial Rd

Oklahoma City, OK 73114

www.byjasco.com

Zigbee is a registered US trademark of the Zigbee Alliance

The Enbrighten logo is a registered trademark of Jasco Products Company, LLC

The images, product information and specifications listed in this document are subject to change